

EARPLUGS

MAXIMUM

Maximum Attenuation. Comfortable Fit.

Overview



Honeywell MAXIMUM earplugs are designed to ensure superior noise blocking performance in a disposable *earplug*. Contoured bell shape for easy insertion.

- The world’s most-used polyurethane foam earplug.
- Improved shape for easy insertion and a better fit.
- Bell shape for maximum in-ear comfort.
- Smooth, soil-resistant skin prevents dirt build-up.
- Corded and Uncorded Bulk refills save time, waste and space.
- NRR 33

Earplug Fitting & Maintenance Recommendations

Inspect: Prior to fitting, examine your earplugs.

Discard: Discard disposable earplugs after each use, or if earplugs are compromised.

Hygiene: To maintain hygiene standards, disposable earplugs should be discarded at the end of every shift.

Fitting:

1. With clean hands, roll the entire earplug into narrowest possible crease-free cylinder.
2. Reach over your head with a free hand, pull your ear up and back, and insert the earplug well inside your ear canal.
3. Hold for 30 – 40 seconds, until the earplug fully expands in your ear canal. If properly fitted, the end of the earplugs should not be visible to someone looking at you from the front.

Improper fit of this device will reduce its effectiveness in attenuating noise. Refer to instructions on package for proper fit.

Recommended Industries/Use

- Agriculture
- Chemical
- Construction
- Fire Protection



- Forestry
- Government
- Law Enforcement
- Manufacturing
- Medical
- Military
- Mining
- Municipal Services
- Oil and Gas
- Pharmaceutical
- Steel and Metals
- Transportation
- Utilities
- Welding

Regulations

- 29 CFR 1910.95 - OSHA Occupational Noise Exposure (US)
- ANSI S3.19-1974 - Attenuation Test Protocol (US)
- Part II, (R.S.C. 1985, c. L-2) - Canada Labour Code
- Z94.2-1994 - Attenuation Test Protocol (CAN)
- 2003/10/EC - EU Hearing Directive
- 89/686/EEC - EC Directive/PPE
- Category II - EC Category/PPE
- EN 352-2:2002 - EU Standards
- NOHSC: 1007 (2000) - National Standard for Occupational Noise (AUS/NZ)
- NR 15 - Security and Health of Work, Annexes 1 and 2, nº3.214/1978 - Occupational Noise Regulations (BR)
- ANSI S12.6/1997 - Method B - Attenuation Test Protocol (BR)
- 9001:2008 - ISO

Specifications

OTHERS

<p>Single Number Rating</p> <ul style="list-style-type: none">• 37 decibel	<p>Corded</p> <ul style="list-style-type: none">• Corded/Uncorded	<p>Certifications; Standards; Specifications Met</p> <ul style="list-style-type: none">• EN 352-2-2002: ANSI S3.19-1974: AS/NZS 1270-2002
<p>Noise Reduction Rating</p> <ul style="list-style-type: none">• 33	<p>Care and Maintenance</p> <ul style="list-style-type: none">• Inspect: Prior to fitting, examine your earplugs.	<p>High Visibility</p> <ul style="list-style-type: none">• Yes
<p>Product Family</p> <ul style="list-style-type: none">• Howard Leight	<p>Earplug Shape</p> <ul style="list-style-type: none">• Bell	<p>SLC80 Rating</p> <ul style="list-style-type: none">• 26 (Class 5)
<p>Earplug Type</p> <ul style="list-style-type: none">• Roll-down Foam	<p>Earplug Size</p> <ul style="list-style-type: none">• One Size Fits All	<p>Canada Class</p> <ul style="list-style-type: none">• A (L)
<p>Reusability</p> <ul style="list-style-type: none">• Disposable• Disposable	<p>Detectable</p> <ul style="list-style-type: none">• No	<p>Cord Color</p> <ul style="list-style-type: none">• Turquoise
<p>Material</p> <ul style="list-style-type: none">• Polyurethane Foam• Polyurethane Foam	<p>Benefits</p> <ul style="list-style-type: none">• MAXIMUM is the World’s Most-Used Polyurethane Foam Earplug. Bell Shape Delivers Maximum in-Ear Comfort. Contoured Design is Easier To Insert. Resists Tendency To Back-Out of Ear	

Product Number

SKUs

SKU	Description
HL400-MAX-REFILL	HL400 Prefilled Canister, Maximum Earplugs, Uncorded, Prefilled Canister Refill for HL400, UOM = CS, 400 Pairs per Canister, 2 Canisters per Case, 800 Pairs per Case
MAX-1	MAXIMUM, Highest attenuating single-use earplug Uncorded, Polybag, UOM = CS, 2000 Pairs per Case, 10 Boxes per Case, 200 Pairs per Box; NSN 6515-01-572- 8338
MAX-1-D	Honeywell Howard Leight Leight Source 500 Contoured Bell Polyurethane Foam Uncorded Earplugs
MAX-30	MAXIMUM, Highest attenuating single-use earplug Corded, Polybag, UOM = CS, 1000 Pairs per Case, 10 Boxes per Case, 100 Pairs per Box; NSN 6515-01-450- 5396
MAX-5-30	MAXIMUM Highest attenuating single-use earplug Corded, 5 Pr Polybag, UOM = CS, 1250 Pairs per Case, 25 Bags per Box, 10 Boxes per Case
MAX-5-H5	MAXIMUM, Highest attenuating single-use earplug Uncorded, 5 Pr Polybag, UOM = CS, 2500 Pairs per Case, 50 Bags per Box, 10 Boxes per Case
MAX-LS4-REFILL	MAXIMUM, Uncorded Dispenser Refill, Highest attenuating single-use earplug, contoured bell shape. Uncorded, Bulk Refill, UOM = CS, 2000 Pairs per Case, 200 Pairs per Bag, 10 Bags per Case

Honeywell
Safety and Productivity
Solutions
855 S Mint St
Charlotte, NC 28202
800-582-4263
www.sps.honeywell.com

MAXIMUM
© 2023 Honeywell International Inc.
All rights reserved.



This document was generated on 2023-05-10 9:38:19 AM (YYYY-MM-DD, HH:mm:ss). Subject to change without notice.

